

fact³

Transparency and sophistication in compact form from the **fact** range



ATLTM

Advanced Transmission Line


www.fact-speakers.com **fact3** in Tiger ebony

The definition of *fact* - **noun** - a thing known to be true with complete certainty

PMC's vast knowledge of acoustic engineering gained from developing the world's leading professional loudspeakers has been distilled into the **fact** range. Only this level of understanding of the creative process, room acoustics and supreme engineering make this possible. Whether mounted on a bookshelf or on its dedicated performance enhancing stand, the **fact3** will confidently express every nuance, bringing you within a hairs breath of the original recording. Its beautifully slender compact cabinet houses PMC's **ATL**TM (Advanced Transmission Line) that takes

its design cues from the world beating IB range that features throughout the highly critical professional world. Combining this style of **ATL**TM (with the ultra high resolution **fact** tweeter and twin **fact** bass drivers creates dramatic scale and deep rich textured bass that no other compact design can achieve. The **fact3** is easy to drive allowing you an unparalleled choice of quality amplification and with its audiophile switching, it guarantees the perfect sound balance in any room with any source combination.

fact³



ATL™

Advanced Transmission Line



Textured fabric meets exotic veneers. Hidden magnets fasten the grille, further enhancing the seamless appearance



fact³ higher compression **ATL™** produces the richest, deepest, and most dynamic bass available for this cabinet size



Take control
HF +1, 0, -1
LF 0, -1, -2
 Audiophile grade switches provide fine-tuning, ensuring the perfect sound balance in any room, and with any source combination



With absolute transparency of audio in mind the **Ag** pure silver coated binding post is the solution

fact³ Specifications

Freq response	35Hz – 30kHz
Sensitivity	89dB 1w 1m
Effective ATL™ (Advanced Transmission Line Length)	1.7m 5.6ft
Impedance	8 Ohms
Drive Units	LF 2 x fact 140mm/5 1/2" precision drivers HF 1 x fact 19mm high-res SONOMEX™ soft dome ferro-fluid cooled
Crossover Freq	1.7 kHz
Input connectors	2 pairs 4mm PMC Ag terminals (Bi-wire or Bi-amp)
Dimensions	H 535mm - 21.0" W 155mm - 6.1" D 300mm - 11.8" + 10mm Grille + 23mm Ag terminal
Weight	9.5 kg 20.9lbs



Front




With grille



Rear




White silk



Rich walnut



Graphite poplar



Tiger ebony



subject to change without notice

PMC HOLME COURT BIGGLESWADE SG18 9ST UK

T +44 (0)870 4441044 F +44 (0)870 4441045

email sales@pmc-speakers.com web www.pmc-speakers.com The Professional Monitor Company Limited Reg No: 3328009 No. 128v3 ©2015

'The trade marks FACT and **fact** are trade marks, and in the United Kingdom, registered trade marks, of The Professional Monitor Company Limited'