



# SPECIFICATIONS

**ci30™**




|                              |  |
|------------------------------|--|
| <b>Freq response</b>         | 47Hz(-3dB)-25kHz   |
| <b>Sensitivity</b>           | 84dB (2.83v @1m)   |
| <b>Effective <i>ATL</i>™</b> | 1.5m (4.9ft)   |
| <b>Impedance</b>             | 8 Ohms   |
| <b>Drive units</b>           | <b>LF</b> 133mm (5.25") Natural Fibre <b>LT</b> ™<br><b>HF</b> 27mm (1") soft dome |
| <b>Input connectors</b>      | 1 pair 4mm sockets   |
| <b>Dimensions</b>            | <b>H</b> 300mm (11.8")<br><b>W</b> 300mm (11.8")<br><b>D</b> 103mm (4")            |
| <b>Weight ea.</b>            | 6.5kg (14lbs)  |

### Horizontal polar response




### Vertical polar response



### Speaker distance calculation table

|                 |                 | Distance from loudspeaker (m) |    |    |
|-----------------|-----------------|-------------------------------|----|----|
|                 |                 | 1                             | 2  | 3  |
| Input power (W) | 1               | 84                            | 78 | 75 |
|                 | 10              | 94                            | 88 | 85 |
|                 | 20              | 97                            | 91 | 88 |
|                 | 50              | 101                           | 95 | 91 |
|                 | Rated max power | 105                           | 99 | 91 |

### On axis frequency response



### Impedance & phase response

